

RACING FUEL “DV8”

PROPERTY	STANDARD UNIT	TEST METHOD	TYPICAL VALUE
Aspect	-	Visual	clear/limpid
Colour	-	Visual	Green
RON	-	EN-ISO 5164	98,5
MON	-	EN-ISO 5163	88,3
Density at 15° C	kg/m ³	EN-ISO 3675	752
Oxygen Content	%wt	Elemental analysis	2,59
Nitrogen Content	%wt	ASTM D 3228	<0,1
Peroxides and nitroxides Content	ppm	ASTM D 3703	<10
Lead Content	g/l	ASTM D 3237	<0,003
Benzene Content	% vol	ASTM D 3606	<0,5
Reid vapour pressure	hPa	ASTM D 323	640
Sulphur content	%wt	EN ISO 20884	<0,005
Aromatic content	%vol	ASTM D 1319	<35
Distillation:			
Evaporated at 70 °C	%vol	ISO 3405	37
Evaporated at 100 °C	%vol		59
Evaporated at 180 °C	%vol		90
Final Boiling Point	°C		185
Residue	%vol		<1,0

Sede Amministrativa:

- 26010 BAGNOLO CREMASCO (CR)
S.S. 235 Km 47+980
Tel. 0373.235111 – Fax 0373.235156

Servizi Racing Fuel:

- Tel. 0373 235141
Fax. 0373.235123

Depositi:

- BAGNOLO CREM. (CR)
- MORTARA(PV)
- PONTSTURA (AL)
- VALMACCA (AL)