



Only for 12h Spa **24H SERIES**

Technical Recommendation

Hankook Slick F200 & Hankook Wet Z207

Tire Size	Compound	Overall diameter	Section width	Circumfer. static
		mm	mm	mm
215/615 R 17	Medium	613	240	1925
215/615 R 17	Hard	613	240	1925
235/620 R 17	Medium	615	252	1932
240/640 R 18	Medium	644	245	2023
240/640 R 18	Hard	644	245	2023
260/660 R 18	Medium	660	282	2073
280/660 R 18	Medium	662	304	2080
280/680 R 18	Medium	680	306	2136
300/660 R 18	Medium	654	330	2055
300/680 R 18	Medium	680	328	2136
320/710 R 18	Medium	706	346	2218
320/710 R 19	Medium	706	348	2218

FWD Cars	Front	Rear
Min. Cold Slick	1.4 bar	1.6 bar
Target Hot	2.1-2.3 bar	2.2-2.5 bar
Max. neg. Cam.	-4°00'	-3°30'
Wet Cold	+0,2 above Slick Pressure	

RWD Cars	Front	Rear
Min. Cold Slick	1.55 bar	1.45 bar
Target Hot	2.2-2.3 bar	2.1-2.3 bar
Max. neg. Cam.	-3°30'	-3°00'
Wet Cold	+0,2 above Slick Pressure	

Remarks

All recommendations depend on racetrack layout, ambient conditions and driver level.
 Sufficient inflation pressure must always be maintained, to avoid structural damage to the tire.
 Please check your rims and valves frequently.
 It is recommended to use valve caps.