

24H SERIES



Hankook Tire Dimension's and technical data's

Dimension	Compound	Diameter	Section Widht Overall	Cirumference Static
215/615R 17	Medium	613	240	1925
215/615R 17	Hard	613	240	1925
235/620R 17	Medium	615	252	1932
240/640 R 18	Medium	644	245	2023
240/640 R 18	Hard	644	245	2023
260/660 R 18	Medium	660	282	2073
270/680 R 18	Medium	685	298	2152
280/650 R 18	Medium	654	306	2055
280/660 R 18	Medium	662	304	2080
300/660 R 18	Medium	654	330	2055
280/710 R 18	Medium	710	306	2231
300/680 R 18	Medium	680	328	2136
320/710 R 18	Medium	706	346	2218
320/710 R 19	Medium	706	348	2218

Tire pressure target :		Minimum cold pressure front :	Minimum cold pressure rear:	Hot pressure: Front Axle / Rear Axle
Front wheel drive:		1,40	1,60	2.1-2,3 bar / 2,2-2,4* bar
Rear wheel drive:		1,50	1,40	2.1-2,3 bar /2.0 - 2.2 bar
Camber :				
Front Axle:				max. 4° 00'
Rear Axle:				max: 3° 30'

WET tire : Generell 0,2 bar higher (cold pressure)