



Hankook Tire Dimension's and technical data's					
Dimension	Compound	Diameter	Widht Overall	Cirumference Static	
215/615R 17	Medium	613	240	1925	
215/615R 17	Hard	613	240	1925	
235/620R 17	Medium	615	252	1932	
240/640 R 18	Medium	644	245	2023	
240/640 R 18	Hard	644	245	2023	
260/660 R 18	Medium	660	282	2073	
270/680 R 18	Medium	685	298	2152	
280/650 R 18	Medium	654	306	2055	
280/660 R 18	Medium	662	304	2080	
300/660 R 18	Medium	654	330	2055	
280/710 R 18	Medium	710	306	2231	
300/680 R 18	Medium	680	328	2136	
320/710 R 18	Medium	706	346	2218	
320/710 R 19	Medium	706	348	2218	
Tire pressure target :		cold pressure front :	Cold pressure Rear:	Hot pressure: / Rear Axle	Front Axle
Front wheel drive:		1,5 - 1,6	1,7- 1,8	2.0-2,2 bar / 2,2-2,4* bar	
Rear wheel drive:		1,4 - 1,5	1,3 - 1,4	1.9-2,0 bar / 1,8 - 1.9 bar	
Camber :					
Front Axle:				max. 4° 00'	
Rear Axle:				max: 3° 30'	
WET tire : Generell 0,2 bar higher (cold pressure)					